

**TECHNICAL PRODUCT SPECIFICATIONS**  
**BRUSSELS**  
**RIGID COMPOSITE VINYL PLANK**

**SPECIFICATIONS:**

STYLE NAME:	BRUSSELS
RECOMMENDED END USE	RESIDENTIAL
FINISH	PREMIUM PROTECT STAIN & SCRATCH RESISTANCE
BACKING	RIGID COMPOSITE BOARD
NOMINAL WEAR LAYER THICKNESS	22 MILS
NOMINAL PRODUCT THICKNESS	5.0 MM
NOMINAL PLANK SIZE	8.03 W X 52.2"L X 0.20" H
PIECES PER CARTON	8
SQUARE FEET PER CARTON	23.29 SQ. FT.
APPROX. WEIGHT PER CARTON	28 LBS.
CARTON SIZE	9" W X 54" L X 2.0"H
CARTONS PER PALLET	56
PALLETS PER CONTAINER	20
SQUARE FEET PER PALLET	1,304.24 SQ. FT.
SQUARE FEET PER 20 FT. CONTAINER	26,084.80 SQ. FT.
APPROX. WEIGHT PER PALLET	1,568 LBS.
APPROX. WEIGHT PER 20 FT. CONTAINER	31,360 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

**PERFORMANCE:**

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.4 K.V. OR LOWER
OTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.74
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1200 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F2753 ROLLING LOADS - PASSES
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 38,000 CYCLES

**INSTALLATION:**

END USE:	RESIDENTIAL
INSTALLATION METHOD:	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED:	UNDERLAYMENT NO MORE THAN 1.5 MM THICKNESS

**WARRANTIES:**

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR AND MANUFACTURING DEFECT WARRANTY
---	---

**CARE & MAINTENANCE:**

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand.  
 For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop