

Specification Sheet



PRODUCT INFORMATION

Construction	Heterogeneous Sheet Flooring
Recommended Usage	ASTM 1303 – Type 1, Grade 1
Total Thickness	80 gauge
Wear Layer Thickness	20 mils
Average Weight	5.55 lbs/yd ²
Wear Layer Treatment	SuperGuard
Backing	HD Mechanical Backing

SIZE & PACKAGING

Width	13' 2"
Standard Length	65'
Average Weight of Standard Roll	527.8 lbs

TECHNICAL INFORMATION

ASTM E662 Smoke Density	< 450
ASTM C1028 COF Slip Resistance	0.74
ASTM F1914 – Residual Indentation	0.007
ASTM F137 – Flexibility	6mm - Passes
ASTM E648 Flooring Radiant Panel	Class 1
ASTM F970 Static Load Limit	750 psi
ASTM F2199 Dimensional Stability with Heat	0.03%
ASTM F1514 – Resistance to Heat	Passes
ASTM F1515 – Resistance to Light	Passes
ASTM F925 – Resistance to Chemicals	Very Good
ASTM E492 IIC Sound Transmission	IIC 44
ASTM 2753 Rolling Load	Excellent
Electrical Resistance EN 1815	≤ 2 kv
Heat Weld Seaming	IVC Commercial Solid Weld Rods

WARRANTY

Limited 10 Year Commercial Warranty

