

FORGED 6mil

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Forged
PRODUCT TYPE	LVT
CONSTRUCTION	Luxury Vinyl Tile
THICKNESS	ASTM F386 - Passes - as specified ± 0.005 "
WEAR LAYER THICKNESS	6 mil (0.15mm)
INSTALLATION METHOD	GlueDown
SIZE	6" x 48"
FINISH	Commercial Urethane Finish
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
SQUARENESS	ASTM F 2421 - Passes - ± 0.10 " max
FLEXIBILITY	ASTM F137 - Passes - 1" Mandrel
DIMENSIONAL STABILITY	Tile ASTM F2055; Plank ASTM F2421 - Passes - ± 0.016 "/linear foot
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
SLIP RESISTANCE	ASTM C1028 - Passes - Wet: greater than/equal to 0.5
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM E649 - Class 1 (> 0.45 W/cm ²)
SMOKE DENSITY	ASTM E662 Part A - Less than 450
OPTIONAL UNDERLAYMENT	AccuSound™, Loose lay, Active Sound-Click
CERTIFICATION	FloorScore® Certified
DESCRIPTION	
INSTALLATION	Glue Down - Peel & Stick - Floating-Click
WARRANTIES	Limited 10 Year Light Commercial Warranty Limited 25 Year Residential Warranty